

V MAX SHO®
25-inch!
250X-SHAFT

V MAX SHO®
25-inch!
150X-SHAFT

NEW



V MAX SHO® Family Expands to Meet the Needs of Many More Anglers and Boaters

The 4.2-litre V6 V MAX SHO family changed the game in the market for high-performance four-stroke outboards. Based on the reality that Yamaha technology can provide a four-stroke that rivals a two-stroke in weight, hole shot and top speed, the V MAX SHO family later expanded to include the V MAX SHO 150. In the spring of 2015, it expands again with the V MAX SHO 115 and the V MAX SHO 175. The new season will also mark the arrival of the V MAX SHO 150 X-Shaft and V MAX SHO 250 X-Shaft.

The addition of a five-inch longer shaft for these models means that the users of multi-species boats can now enjoy the benefits for which the V MAX SHO has become famous. The X-Shaft models are also perfect for a variety of other applications that require a 25-inch shaft length.

V MAX SHO 250 *25-inch!*

This is the outboard that started it all, offering outrageously light weight and outstanding performance with all the attributes of a four stroke – thus changing the game. While originally envisioned as a bass boat solution, it has found a following among many other boaters as well. Now, it comes with a 25-inch shaft for multi-species and other applications.

UNTOUCHED TECHNOLOGY

- ▶ The V MAX SHO 250 has 4.2-litre big-bore V6 displacement thanks to plasma-fused sleeveless cylinders. With it, displacement is increased without enlarging the outer diameter of the cylinder, resulting in an outboard with the largest displacement in its class. That technology also contributes to light weight.



Available Models: VF250XA, VF150XA

YAMAHA



V MAX SHO® 250 ^{25-inch!}X-SHAFT / 150 ^{25-inch!}X-SHAFT

EFFECTIVE OCTOBER 6, 2014

▶ **UNEQUALED PERFORMANCE/HOLE SHOT**

The V MAX SHO 250 has instant throttle response, especially in the mid-range, for performance you can feel.

▶ **OUTSTANDING EFFICIENCY**

The V MAX SHO 250 burns an average of 12 percent less fuel than a comparable direct-injection two stroke. That fuel efficiency is hard to beat. At the same time, with no need to carry two-stroke oil, the available space in the boat can be used more efficiently. It opens up a whole compartment in the boat for batteries or storage.

▶ **UNPARALLELED GOOD MANNERS**

It's a Yamaha four stroke, which means it is quiet. Go ahead – have a conversation at wide open throttle. Thanks to features such as advanced four valves per cylinder and precision components, the outboard operates smoothly.

V MAX SHO 150 *25-inch!*

Whether you are running flats boats, bass boats, pontoons, or now, multi-species boats, the V MAX SHO 150 truly delivers the performance you have come to expect from a Yamaha V MAX SHO while providing all the benefits associated with four-stroke power, including clean, quiet operation and great fuel efficiency.

▶ **TWO-STROKE PERFORMANCE**

Yamaha's Variable Camshaft Timing System (VCT) helps the 2.8-litre inline four develop lots of power in the midrange of the power curve for great overall performance as well as top speed.

▶ **TRADITIONAL FOUR-STROKE BENEFITS**

It's super smooth and powerful, thanks to advanced double overhead cams, four valves per cylinder and counterbalance shafts. The V MAX SHO is also extremely fuel-efficient, delivering 30 to 40 percent better fuel efficiency than a carbureted two stroke.

▶ **YAMAHA CONVENIENCE**

The V MAX SHO 150 allows more efficient use of space in the boat because it does not require carrying two-stroke oil. There's no need for a tank, which means more room for batteries or storage. With mechanical control, the outboard offers easy rigging. You can equip it with your choice of analog, 6Y5 digital or Command Link® gauges.

▶ **EASIER FISHING**

The V MAX SHO 150 X Shaft is compatible with Yamaha's variable trolling RPM switch (VTS), which allows anglers to adjust the trolling speed in 50 RPM increments from 650 to 900 RPM using a Yamaha Command Link gauge.

**V MAX SHO® 250** *25-inch!* X-SHAFT / **150** *25-inch!* X-SHAFT

EFFECTIVE OCTOBER 6, 2014

Specifications: V MAX SHO 150 X-Shaft

ENGINE

| | |
|--------------------------------|-------------------------------|
| Type | In-Line Four-Cylinder |
| Displacement | 2,785 cc (170 ci) |
| Bore x Stroke | 96 x 96.2 mm (3.78 x 3.79 in) |
| Full Throttle RPM Range | 5,000 ~ 6,000 |
| Variable Trolling RPM Range | 650 ~ 900 |
| Horsepower Rating at Propshaft | 150 hp at 5500 rpm |
| Compression Ratio | 10.3:1 |
| Fuel Induction/Scavenging | EFI (DOHC) |
| Alternator Output | 50 Amp |
| Starting Method | Electric w/ PTT |
| Ignition | TCI Microcomputer |
| Lubrication | Wet Sump |
| Degree of Trim | -4° through +16° |
| Degree of Tilt | 70° |
| Exhaust | Through Propeller |
| Cooling | Thermostatic Control |

DRIVE

| | |
|----------------|------------|
| Gear Shift | F-N-R |
| Gear Ratio | 2.00:1 |
| Control Method | Mechanical |

SHAFT LENGTH

See Model Code X=25"

FUEL AND LUBRICATION

| | |
|---------------------|--|
| Recommended Fuel | Regular Unleaded (Minimum Pump Octane 89) |
| Recommended Oil | Yamalube® 4M (See Owner's Manual) |
| Engine Oil Capacity | 4.5 L / 4.3 L w/without filter |

LIMITED WARRANTY

| | |
|-----------------|-------------|
| Pleasure | Three Years |
| Camp/Government | Two Years |
| Commercial | One Year |

WEIGHT

222 kg / 489 lb*

*Weight estimated at time of publishing. Weight is measured without motor oil, gearcase oil and propeller (except on models that include standard propeller.)

Features

POWER/PERFORMANCE

- Lightweight, Compact, Powerful Design
- 2.8 L High Output Four Cylinder
- Variable Camshaft Timing System (VCT)
- 4 Large-Diameter Valves Per Cylinder
- Double Overhead Camshafts
- Tuned Long-Track Induction System

RELIABILITY/DURABILITY

- TCI Microcomputer Ignition System
- Wet Sump Lubrication
- Engine Warning System
- Water Separator
- Direct Coil-in-Cap Ignition System
- Sacrificial Anodes
- High Output Alternator
- Electronic Single Throttle Valve Intake System
- YDC-30 Aluminum Alloy
- Phaze Five™ Paint System

CONVENIENCE/CONTROL

- Easy Maintenance
- Command Link or Analog Gauge Compatibility
- Power Trim & Tilt
- Variable Trolling RPM Switch (VTS)
- Freshwater Flush
- Vibration Reduction Mounting System
- Mechanical Controls
- Easy-Access, Self-Draining Oil Filter

V MAX SHO® 250 ^{25-inch!}X-SHAFT / 150 ^{25-inch!}X-SHAFT

EFFECTIVE OCTOBER 6, 2014

Specifications: V MAX SHO 250 X-Shaft

ENGINE

| | |
|--------------------------------|-----------------------------|
| Type | 60° V6 |
| Displacement | 4.2 Litre |
| Bore x Stroke | 96 x 96 mm (3.78 x 3.78 in) |
| Full Throttle RPM Range | 5,000 ~ 6,000 |
| Horsepower Rating at Propshaft | 250 hp at 5,500 rpm |
| Compression Ratio | 10.3:1 |
| Fuel Induction/Scavenging | EFI / VCT / DOHC |
| Alternator Output | 50 Amp / 46 Amp @ 1,000 rpm |
| Starting Method | Electric w/ PTT |
| Ignition | TCI Microcomputer |
| Lubrication | Wet Sump |
| Degree of Trim | -3° through +16° |
| Degree of Tilt | 66° |
| Exhaust | Through Propeller |
| Cooling | Thermostatic Control |

DRIVE

| | |
|----------------|------------|
| Gear Shift | F-N-R |
| Gear Ratio | 1.75:1 |
| Control Method | Mechanical |

SHAFT LENGTH

See Model Code X=25"

FUEL AND LUBRICATION

| | |
|---------------------|--|
| Recommended Fuel | Regular Unleaded (Minimum Pump Octane 89) |
| Recommended Oil | Yamalube® 4M (See Owner's Manual) |
| Engine Oil Capacity | 6.7 L / 6.4 L w/without filter |

LIMITED WARRANTY

| | |
|-----------------|-------------|
| Pleasure | Three Years |
| Camp/Government | Two Years |
| Commercial | One Year |

WEIGHT

252 kg / 555 lb*

*Weight estimated at time of publishing. Weight is measured without motor oil, gearcase oil and propeller (except on models that include standard propeller.)

Features

POWER/PERFORMANCE

- Super High Output 60° V6 Design
- Mechanically Controlled Four-Stroke V6 Outboard
- Plasma-Fused Sleeveless Cylinders
- Variable Camshaft Timing System (VCT)
- Long Track Induction System
- Electronic Multi-Point Precision Fuel Injection
- Ignition Knock Sensor

RELIABILITY/DURABILITY

- TCI Microcomputer
- Wet Sump Lubrication
- Engine Warning System
- Water Separator
- Direct Drive System
- Direct Ignition
- Sacrificial Anodes
- High Output Alternator
- Electronic Single Throttle Valve (75 mm)
- Water Cooled Rectifier/Regulator
- Phaze Five Paint System

CONVENIENCE/CONTROL

- Easy Maintenance
- Command Link Gauges
- Optional Tilt Limiter
- Power Trim & Tilt
- Freshwater Flush
- Vibration Reduction Mounting System
- Single Timing Belt System
- Yamaha Diagnostic System
- Easy-Access, Self-Draining Oil Filter

REMEMBER to always observe all applicable boating laws. Never drink and drive. Dress properly with USCG-approved personal flotation device and protective gear. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any reference to other companies or their products are for identification purposes only, and are not intended to be an endorsement. Due to Yamaha's ongoing commitment to product improvement, we reserve the right to change without notice, equipment, materials, specifications or prices. The information and data contained herein is approximate and subject to many factor and variables, including but not limited to atmospheric, water and equipment conditions and operator ability. Therefore, such information and data is provided as a guideline only. © 2014 Yamaha Motor Canada Ltd. All rights reserved.